

Parts List and Operating Instructions

PestPro 2000 Backpack Sprayer

SAFETY PRECAUTIONS

- Do not adjust the tip when the tank is pressurized.
- Do not transport the sprayer while it is under pressure.
- Do not fill with or spray flammable, acid, or caustic liquids.
- Sprayer filled with liquid is heavy, use caution when bending, leaning, or walking. Bend at the knees and not the waist.

SUGGESTED USES:

This sprayer can be used to apply water-based insecticide to exterior and some interior surfaces for the control of crawling insects. It can also be used to treat mosquito resting sites on vegetation.

OPERATING INSTRUCTIONS

Filling and Mixing

- Mix all insecticides with the proper amount of water in a separate container.
- Add the liquid insecticide to the tank; then pump the sprayer handle to prime the pump and fill the pressure cylinder. The liquid in the tank will decrease as the cylinder is filled. Add more liquid to fill the tank.

Remaining Liquid

Unused insecticide dilution in the tank should be removed and stored properly.

CARE AND MAINTENANCE

Note: Residue from wettable powder (WP), soluble powder (SP) and some flowable (F) formulations can obstruct the pump cylinder and valve of the PestPro Sprayer. Regular cleaning with clean water is required to keep the unit operating properly. Consider weekly cleaning when the unit is in daily use. Rinse the tank with clean water, then add clean water to tank, pressurize and flush the hose and valve for several minutes

SYMPTOMS	SOLUTIONS
Tank not holding pressure	<ul style="list-style-type: none"> • Check the gasket inside the tank cap, lubricate when dry.
No spray produced at the nozzle	<ul style="list-style-type: none"> • Tighten the cap to seal tank. • Check the nozzle for blockage.
Liquid leaking at the back of the nozzle	<ul style="list-style-type: none"> • Remove end of tip and check the o-ring, clean the opening on the inside. • Inspect and replace gasket in Multiejet valve.
Handle locks up like tank is full of pressure	<ul style="list-style-type: none"> • Remove hose from tank and pump unit to release air pocket.

REPLACEMENT PARTS

Hose Assembly	33000309
XR-Gun	22037500
Brass Extension	22045600
Check Valve/Strainer	22032551
5850-CC Crack & Crevice Tip Assembly	22049466
5850 4-Way Tip Assembly	22049451
8004 Celcon Tip	22032149
Brass AV-210	23083602